



## BENTWOOD 5.0 AH127

### PRODUCT SPECIFICATIONS

|                         |                                                                             |
|-------------------------|-----------------------------------------------------------------------------|
| STYLE NAME / NUMBER     | Bentwood 5.0 / AH127                                                        |
| PRODUCT TYPE            | LVT                                                                         |
| COLLECTION NAME         | Bentwood                                                                    |
| CONSTRUCTION            | Luxury Vinyl Tile                                                           |
| INSTALLATION METHODS    | BrickAshlar, VerticalAshlar, Herringbone                                    |
| GAUGE                   | 5 mm                                                                        |
| FINISH                  | Enhanced Urethane                                                           |
| CLASSIFICATION          | (ASTM F1700) Type B - Embossed                                              |
| SIZE AND TOLERANCE      | (ASTM F 2421) Passes                                                        |
| FLEXIBILITY             | (ASTM F2199) Passes                                                         |
| DIMENSIONAL STABILITY   | Plank ASTM F2421 - Passes - $\pm 0.016''$ /linear foot                      |
| RESIDUAL INDENTATION    | (ASTM F1914) Passes                                                         |
| RESISTANCE TO CHEMICALS | (ASTM F925) Passes                                                          |
| RESISTANCE TO HEAT      | (ASTM E649) $> 0.45$ W/cm <sup>2</sup>                                      |
| SMOKE DENSITY           | (ASTM F1515) Passes                                                         |
| WARRANTIES              | Limited 10 Year Commercial Warranty<br>Limited 25 Year Residential Warranty |

*For additional technical information, please contact Technical Services at **800.833.6954**.*